

CERTIFICATE OF ANALYSIS

Product: **Buffer, Reference Standard, pH = 4.00 (Red)** *Date of Manufacture:* 11/7/24

Expiration Date: February 2027

Intended Use: Calibration of pH Meters. Recommended Storage: 15 to 25 °C (59 to 77 °F)

Product Code: CP-C1228P, CP-A1228P Lot Number: **8505110**

Country of Origin United States of America

This solution is traceable to the NIST Standard Reference Materials (SRMs) Potassium Dihydrogen Phosphate (186-I),

Disodium Hydrogen Phosphate (186-II) and Potassium Hydrogen Phthalate (185).

Test Specification Result

pH at 25°C 3.99 - 4.01 4.01

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Quality Control, Certifying Officer

wasai Rom



CERTIFICATE OF ANALYSIS

Product: Silver Nitrate, 0.10 N Date of Manufacture: 4/24/25

Expiration Date: May 2027

Intended Use: General Laboratory Reagent/Chemical. Recommended Storage: 15 to 25 °C (59 to 77 °F)

 Product Code:
 CP-B2248P, CP-E2248, CP-C2248P
 Lot Number:
 8505112

Country of Origin United States of America

Standardized against NIST SRM Sodium Chloride, 919

Test	Specification	Result	
Appearance Assay (vs. Sodium Chloride)	Colorless 0.0995 - 0.1005Normal	Colorless 0.1001Normal	

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Quality Control, Certifying Officer

wasai Rom