

Version 3

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 2025-06-30

#### SISECTION 1.Identification

#### **Product identifier**

Product number CP-C1305

Product name Chloroform,(Ethanol Stabilized)

Synonyms TCM, Trichloromethane

CAS-No. 67-66-3

## Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis in the laboratory

## Details of the supplier of the safety data sheet

Company ChemPure Brand Chemicals

39103 Warren Road Westland, MI 48185 L

Westland, MI 48185 USA Phone: 1-734-884-4773

Emergency telephone 800-424-9300 CHEMTREC (USA) 24 Hours/day; 7 Days/week

+1-703-527-3887 CHEMTREC (International)

## SECTION 2. Hazards identification

## **GHS Classification**

Acute toxicity, Category 4, Oral, H302

Acute toxicity, Category 3, Inhalation, H331

Skin irritation, Category 2, H315 Eye irritation, Category 2A, H319

Carcinogenicity, Category 2, H351

Reproductive toxicity, Category 2, H361

Specific target organ systemic toxicity - repeated exposure, Category 1, Liver, Kidney, H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **GHS-Labeling**

Hazard pictograms







Signal Word
Danger

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305 Version 3

Product name Chloroform (Ethanol Stabilized)

#### Hazard Statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.

#### Precautionary Statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P311 Call a POISON CENTER/doctor.

P321 Specific treatment (see supplemental first aid instructions on this label).

P330 Rinse mouth.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

## SECTION 3. Composition/information on ingredients

Formula CHCl₃ CHCl₃ (Hill)

Synonyms TCM

Molar mass 119.38 g/mol

#### Hazardous ingredients

Chemical name (Concentration)

CAS-No.

Chloroform (>= 90 % - <= 100 %)

67-66-3

Exact percentages are being withheld as a trade secret.

ethanol (>= 1 % - < 5 %)

64-17-5

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305

Product name Chloroform (Ethanol Stabilized)

Exact percentages are being withheld as a trade secret.

#### **SECTION 4. First aid measures**

## Description of first-aid measures

General advice

First aider needs to protect himself.

Inhalation

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

Skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower. Consult a physician.

Eve contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist.

Ingestion

After swallowing: caution if victim vomits. Risk of aspiration! Keep respiratory tract clear. Pulmonary failure possible after aspiration of vomit. Call a physician immediately. Subsequently administer: activated charcoal (20 - 40 g in 10% slurry).

Never give anything by mouth to an unconscious person.

## Most important symptoms and effects, both acute and delayed

irritant effects, Cough, Shortness of breath, respiratory arrest, Dizziness, narcosis, agitation, spasms, inebriation, Nausea, Vomiting, Stomach/intestinal disorders, cardiovascular disorders, Headache, ataxia (impaired locomotor coordination)

Drying-out effect resulting in rough and chapped skin.

#### Indication of any immediate medical attention and special treatment needed

Laxative: Sodium sulfate (1 tablespoon/1/4 I water).

## **SECTION 5. Fire-fighting measures**

#### Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

#### Special hazards arising from the substance or mixture

Not combustible.

Ambient fire may liberate hazardous vapors.

Fire may cause evolution of:

Hydrogen chloride gas, Phosgene

#### Advice for firefighters

Special protective equipment for fire-fighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

CP-C1305 Product number Chloroform (Ethanol Stabilized)

Product name

#### Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### SECTION 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

## **Environmental precautions**

Do not empty into drains.

#### Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area. Do not inhale vapors.

## **SECTION 7. Handling and storage**

#### Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapors/aerosols.

Observe label precautions.

## Conditions for safe storage, including any incompatibilities

Protected from light. Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Store at room temperature.

#### SECTION 8. Exposure controls/personal protection

#### Exposure limit(s)

Ingredients

Threshold Remarks Basis Value

limits

Chloroform 67-66-3

**ACGIH** Time Weighted Average 10 ppm

(TWA):

NIOSH/GUIDE Short Term Exposure 2 ppm

Limit (STEL): 9.78 mg/m<sup>3</sup>

OSHA\_TRANS Ceiling Limit Value: 50 ppm 240 mg/m<sup>3</sup>

Z<sub>1</sub>A Time Weighted Average 2 ppm

9.78 mg/m<sup>3</sup> (TWA):

ethanol 64-17-5

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305 Version 3
Product name Chloroform (Ethanol Stabilized)

ACGIH Short Term Exposure 1,000 ppm Limit (STEL):

NIOSH/GUIDE Recommended 1,000 ppm exposure limit (REL): 1,900 mg/m³

OSHA\_TRANS PEL: 1,000 ppm

1,900 mg/m<sup>3</sup>

Z1A Time Weighted Average 1,000 ppm

(TWA): 1,900 mg/m<sup>3</sup>

## **Engineering measures**

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

## Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

#### Hygiene measures

Immediately change contaminated clothing. Apply skin- protective barrier cream. Wash hands and face after working with substance.

Eye/face protection

Safety glasses

Hand protection

full contact:

Glove material: Viton (R)
Glove thickness: 0.70 mm
Break through time: > 480 min

splash contact:

Glove material: butyl-rubber
Glove thickness: 0.7 mm
Break through time: > 10 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 890 Vitoject® (full contact), KCL 898 Butoject® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment:

protective clothing

Respiratory protection

required when vapors/aerosols are generated.

Recommended Filter type: Filter AX (EN 371)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are performed according to the instructions of the producer. These measures have to be properly documented.

Product number Product name CP-C1305

Chloroform (Ethanol Stabilized)

Version 3

## SECTION 9. Physical and chemical properties

Physical state liquid

Color colorless

Odor sweet

Odor Threshold 84.9 - 201.5 ppm

pH No information available.

Melting point -81 °F (-63 °C)

Boiling point/boiling range ca. 142 °F (61 °C)

at 1,013 hPa

Flash point Method: DIN 51755 Part 1

does not flash

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit Not applicable

Upper explosion limit Not applicable

Vapor pressure 211 hPa

at 68 °F (20 °C)

Relative vapor density 4.25

Density 1.48 g/cm<sup>3</sup>

at 68 °F (20 °C)

Relative density No information available.

Water solubility 8.7 g/l

at 73 °F (23 °C)

Method: OECD Test Guideline 105

Partition coefficient: n-

octanol/water

log Pow: 2 (25 °C) (experimental)

(IUCLID) Bioaccumulation is not expected.

Autoignition temperature No information available.

Decomposition temperature Distillable in an undecomposed state at normal pressure.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305 Version 3
Product name CP-C1305 Chloroform (Ethanol Stabilized)

Viscosity, dynamic 0.57 mPa.s

at 68 °F (20 °C)

Explosive properties Not classified as explosive.

Oxidizing properties none

Ignition temperature not combustible

## SECTION 10. Stability and reactivity

## Reactivity

See below

## Chemical stability

heat-sensitive Sensitivity to light

Stabilizer ethanol

## Possibility of hazardous reactions

Risk of explosion with:

Ammonia, Amines, nitrogen oxides, bases, Oxygen, alkali amides, organic nitro compounds, strong alkalis, Fluorine, peroxi compounds, Alkaline earth metals, Alkali metals, Powdered metals

Methanol, with, alcoholates

Methanol, with, strong alkalis

Iron, in powder form

various alloys, sensitive to shock

Methanol, with, Sodium hydroxide

magnesium, in powder form

Oxygen, with, alkali compounds

Aluminum, in powder form

Acetone, with, alkali compounds

Potassium, sensitive to shock

sodium, sensitive to shock

Violent reactions possible with:

phosphines, bis(dimethylamino)dimethyl tin, nonmetallic hydrogen compounds, Powdered metals, Light metals, Ketones, mineral acids, Strong oxidizing agents, semimetallic hydrogen compounds

#### Conditions to avoid

no information available

## Incompatible materials

rubber, various plastics

## Hazardous decomposition products

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

CP-C1305

Product name Chloroform (Ethanol Stabilized)

Version 3

in the event of fire: See section 5.

## **SECTION 11. Toxicological information**

## Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact

Target Organs

Heart

Eyes

Liver

Kidneys

Skin

Central nervous system

Respiratory system

Blood

reproductive system

Acute oral toxicity

LD50 Rat: 695 mg/kg (RTECS)

absorption

Symptoms: Nausea, Vomiting, Risk of aspiration upon vomiting., Aspiration may cause

pulmonary edema and pneumonitis.

Acute inhalation toxicity

Acute toxicity estimate: 0.5 mg/l; aerosol

Symptoms: Cough, Shortness of breath, Possible damages:, mucosal irritations

absorption

Acute dermal toxicity

LD50 Rabbit: > 3,980 mg/kg

(IUCLID)

absorption

Skin irritation

Rabbit

Result: slight irritation

(IUCLID)

Drying-out effect resulting in rough and chapped skin.

Causes skin irritation.

Eye irritation

Causes serious eye irritation.

Genotoxicity in vitro

Ames test

Salmonella typhimurium

Result: negative

Method: OECD Test Guideline 471

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305
Chloroform (Ethanol Stabilize

Product name Chloroform (Ethanol Stabilized)

Carcinogenicity

Carcinogen classifications of IARC, NTP, California proposition 65 for Ethanol CAS 64-17-5 apply to beverage use only. This product is NOT intended for this use.

CMR effects

Carcinogenicity: Suspected of causing cancer.

Teratogenicity / Reproductive toxicity: Suspected of damaging fertility or the unborn child.

Specific target organ systemic toxicity - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific target organ systemic toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Target Organs: Liver, Kidney

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC Group 2B: Possibly carcinogenic to humans

Chloroform 67-66-3

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP Anticipated carcinogen.

Chloroform 67-66-3

ACGIH Confirmed animal carcinogen with unknown relevance to

humans.

Chloroform 67-66-3

**Further information** 

Systemic effects:

After absorption:

Dizziness, inebriation, agitation, spasms, narcosis, respiratory arrest

After long-term exposure to the chemical:

drop in blood pressure, Headache, ataxia (impaired locomotor coordination), Stomach/intestinal

disorders, cardiovascular disorders

Damage to:

Liver, Kidney, Cardiac

Effect potentiated by: ethanol

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

## **SECTION 12. Ecological information**

## **Ecotoxicity**

Toxicity to fish

LC50 Lepomis macrochirus (Bluegill sunfish): 18 mg/l; 96 h (IUCLID)

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 79 mg/l; 48 h (IUCLID)

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

CP-C1305 Product number

Chloroform (Ethanol Stabilized) Product name

EC5 E.sulcatum: > 6,560 mg/l; 72 h (IUCLID) (maximum permissible toxic concentration)

Toxicity to algae

IC5 Scenedesmus quadricauda (Green algae): 1,100 mg/l; 8 d (IUCLID) (maximum permissible

toxic concentration)

Toxicity to bacteria

EC5 Pseudomonas putida: 125 mg/l; 16 h (IUCLID) (maximum permissible toxic concentration)

EC50 activated sludge: 1,010 mg/l; 3 h

**OECD Test Guideline 209** 

## Persistence and degradability

Biodegradability

0 %: 14 d **OECD Test Guideline 301C** 

Not readily biodegradable.

## Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: 2 (25 °C) (experimental)

(IUCLID) Bioaccumulation is not expected.

#### Mobility in soil

Distribution among environmental compartments

Adsorption/Soil log Koc: 1.72 (experimental) Mobile in soils

#### Other adverse effects

Henry constant 14084 Pa\*m3/mol Method: (experimental)

(IUCLID) Distribution preferentially in air.

## **SECTION 13. Disposal considerations**

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Page 10 of 14

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305

Product name Chloroform (Ethanol Stabilized)

Version 3

#### **SECTION 14. Transport information**

Land transport (DOT)

UN number UN 1888

Proper shipping name CHLOROFORM

Class 6.1
Packing group III
Environmentally hazardous --

Air transport (IATA)

UN number UN 1888

Proper shipping name CHLOROFORM

Class 6.1
Packing group III
Environmentally hazardous -Special precautions for user no

Sea transport (IMDG)

UN number UN 1888

Proper shipping name CHLOROFORM

Class 6.1
Packing group III
Environmentally hazardous -Special precautions for user
EmS yes
F-A S-A

## **SECTION 15. Regulatory information**

## **United States of America**

#### **SARA 313**

The following components are subject to reporting levels established by SARA Title III, Section 313:

Ingredients

Chloroform 67-66-3 *99* %

#### **SARA 302**

The following components are subject to reporting levels established by SARA Title III, Section 302:

Ingredients

Chloroform 67-66-3

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

CP-C1305 Product number

Chloroform (Ethanol Stabilized) Product name

#### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Ingredients

Chloroform

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Inaredients

Chloroform

**DEA List I** 

Not listed

**DEA List II** 

Not listed

## **US State Regulations**

## Massachusetts Right To Know

Ingredients

Chloroform

ethanol

## Pennsylvania Right To Know

Ingredients

Chloroform

ethanol

## **New Jersey Right To Know**

Ingredients

Chloroform

ethanol

## California Prop 65 Components

WARNING: this product contains a chemical known in the State of California to cause cancer.

Ingredients

Chloroform

## California Prop 65 Components

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Ingredients

Chloroform

## **Notification status**

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL

#### **SECTION 16. Other information**

Product number Product name CP-C1305

Chloroform (Ethanol Stabilized)

Version 3

## Training advice

Provide adequate information, instruction and training for operators.

## Labeling

Hazard pictograms





# Signal Word Danger

#### Hazard Statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.

#### Precautionary Statements

## Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

For use in industrial installations only.

## Full text of H-Statements referred to under sections 2 and 3.

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated
	exposure.

#### Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date 2025-06-30

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number CP-C1305 Version 3
Product name Chloroform (Ethanol Stabilized)

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.